IN THE CLAIMS:

Please amend the claims as follows:

- 1. (Currently Amended) A liquid crystal display device, comprising:
 - a liquid crystal display panel;

a backlight unit having a light guideplate, a fluorescent lamp, a reflection sheet substantially enclosing the fluorescent lamp to reflect light emitted from the fluorescent lamp, and a bottom cover having an end portion that is in contact with opposing sides of the reflection sheet to substantially surround and encase the reflection sheet and to support and affix the reflection sheet, the reflection sheet enclosing an outer side of the florescent lamp except for a light exit portion of the fluorescent lamp and overlapping a portion of the light guide plate; and a chassis supporting and affixing the liquid crystal display panel and the backlight unit.

- 2. (Previously Presented) The device according to claim 1, wherein the backlight unit further comprises:
 - a panel-type light guide plate having a light projection plane and a light incident plane; a reflection plate along a rear side of the light guide plate;
- a lamp assembly at the light incident plane of the light guide plate, the lamp assembly including the fluorescent lamp and the reflection sheet at an outer side of fluorescent lamp;
 - at least one optical sheet over the light projection plane of the light guide plate; and a rectangular mold frame receiving the reflection plate, the light guide plate, the optical

sheet, and the lamp assembly therein,

wherein the bottom cover extends from a bottom of the mold frame to an outer side of the reflection sheet.

- 3. (Canceled).
- 4. (Previously Presented) The device according to claim 2, wherein the reflection sheet has a round shape and end portions of the reflection sheet overlap a portion of the light guide plate by a first overlap amount.
- 5. (Original) The device according to claim 4, wherein the first overlap amount is within a range of about 0.2 mm to about 30 mm.
- 6. (Original) The device according to claim 1, wherein the reflection sheet is formed of one of a synthetic resin selected from the group consisting of alkylbenzene sulfonate (ABS), polyethylene terephthalate (PET), and polyvinyl chloride (PVC), and a non-metallic substance.
- 7. (Original) The device according to claim 6, wherein the synthetic resin includes one of a polymer having a high reflexibility and Ti.
- 8. (Original) The device according to claim 2, wherein an extension portion of the reflection plate forms the reflection sheet.

- 9. (Previously Presented) The device according to claim 1, wherein the end portion of the bottom cover has a round shape.
- 10. (Previously Presented) The device according to claim 2, wherein a space between the end portion of the bottom cover and the light guide plate is within a range of about 0.1 mm to about 50 mm.
- 11. (Currently Amended) A backlight unit, comprising:
 - a panel-type light guide plate having a light projection plane and a light incident plane; a reflection plate along a rear side of the light guide plate;
- a lamp assembly at the light incident plane of the light guide plate, the lamp assembly including the fluorescent lamp and a reflection sheet at an outer side of fluorescent lamp;
- at least one optical sheet over the light projection plane of the light guide plate; and a bottom cover extending from a rear side of the reflection plate to an outer side of the reflection sheet such that an end portion of the bottom cover extends to the outer side of the reflection sheet and is in contact with opposing sides of the reflection sheet to substantially surround and encase the reflection sheet and to support and affix the reflection sheet, the reflection sheet enclosing an outer side of the florescent lamp except for a light exit portion of the fluorescent lamp and overlapping a portion of the light guide plate.

Attorney Docket No. 041993-5363 Application No.: 10/751,477

Page 5

Page 5

12. (Original) The device according to claim 11, wherein the reflection sheet is formed of one of

a synthetic resin selected from the group consisting of alkylbenzene sulfonate (ABS),

polyethylene terephthalate (PET), and polyvinyl chloride (PVC), and a non-metallic substance.

13. (Original) The device according to claim 12, wherein the synthetic resin includes one of a

polymer having a high reflexibility and Ti.

14. (Original) The device according to claim 11, wherein an extension portion of the reflection

plate forms the reflection sheet.

15. (Previously Presented) The device according to claim 11, wherein the end portion of the

bottom cover has a round shape.

16. (Canceled).

17. (Previously Presented) The device according to claim 11, wherein end portions of the

reflection sheet overlap a portion of the light guide plate by a first overlap amount within a range

of about 0.2 mm to about 30 mm and a space between the end portion of the bottom cover and

the light guide plate is within a range of about 0.1 mm to about 50 mm.

1-WA/2817961.1

Page 6

18. (Currently Amended) A backlight unit for a liquid crystal display device, comprising:

a light guide plate;

a reflection plate along a rear side of the light guide plate;

a fluorescent lamp along an outer periphery of the light guide plate;

a reflection sheet substantially enclosing the fluorescent lamp along the outer periphery of

the light guide plate to reflect light from the fluorescent lamp to the light guide plate; and

a bottom cover along a rear side of the reflection plate having an end portion that is in

contact with opposing sides of the reflection sheet to substantially surround and encase the

reflection sheet and to support and affix the reflection sheet, the reflection sheet enclosing an

outer side of the florescent lamp except for a light exit portion of the fluorescent lamp and

overlapping a portion of the light guide plate.

19. (Previously Presented) The backlight unit according to claim 18, wherein a first end portion

of the reflection sheet overlaps a portion of the reflection plate and a second end portion of the

reflection sheet overlaps a portion of the light guide plate.

20. (Currently Amended) The backlight unit according to claim 18, wherein an extension

portion of the reflection plate forms the reflection sheet and overlaps a portion of the light-guide

plate.